



Page 1 of 2

Heat of Rejection for AC Load - MAF - 11,580 BTU/h
MWF - 1785 BTU/h

Performance Data KML-600MAF/MWF:

Ambient Temp (F°)		70		80		90		100	
	Water Temp.	Air	Water	Air	Water	Air	Water	Air	Water
Production 24 hours	50	631	572	605	553	575	547	540	535
	70	596	547	551	515	513	488	499	486
	90	542	534	492	513	455	481	401	475
Cycle Time Freeze	50	20	21	21 21	22	22	24	22	
	70	21	22	23 22	24	23	25	23	
	90	24	23	26 24	27	25	30	26	
Cycle Time Harvest	50	3.5	3.9	3.2	3.6	2.9	3.5	2.5	3.5
	70	3.1	3.5	2.5	2.9	2.0	2.5	2.0	2.4
	90	2.9	3.2	2.6 2.8	2.0	2.2	2.0	2.0	
Pressure High Side	50	250	270	266 272	280 272	310	275		
	70	271	272	298 275	320 278	328	280		
	90	302	280	332 285	354 287	385	295		
Pressure Low Side	50	38	35	40 36	41	36	24	39	
	70	41	36	45 37	48	38	49	40	
	90	47	42	51	46	54 46	60	53	

Wiring Diagram KML-600M Series:

