



HXR1A/2A-FGE

Full Glass Door, Laboratory/Pharmacy Refrigerator

Certified to NSF/ANSI 456 Vaccine Storage Standard



HXR1A/2A-FGE

06/04/26

Item # 13599




HXR1A-FGE



HXR2A-FGE

Monitoring display with user-friendly interface

- o 7-inch capacitive multi-touch digital display is user-programmable with temperature in °C or °F
- o Intuitive event and data logging capability with easy download via convenient, front access USB port



- **Designed for performance**
 - o Modular refrigeration system with microprocessor controller provides reliable performance
 - o Thermostatic Expansion Valve (TXV) system quickly and effectively regulates refrigerant flow to control temperatures
 - o Unique ducted air distribution system maintains uniform temperature for consistent cabinet temperatures at each shelf level
 - o Auto-evaporating condensate pan means no overflow or mess
- **Durable construction**
 - o Stainless steel interior and exterior front, sides and top provide resistance to rust and corrosion and is easy to clean
 - o Evaporator coils are epoxy electrocoated to help fight corrosion
 - o Heavy duty, easy to roll casters (two with locks)
- **Energy efficient and sustainable**
 - o Energy efficient LED lights (full length)
 - o Environmentally friendly R290 hydrocarbon refrigerant
 - o 2 3/8" of CFC-free foamed in place insulation
- **Product Safety**
 - o Audible and visual alarms for high/low temperature, door open, power failure, and low battery
 - o Dry contacts for remote alarming
 - o Standard access port for third party temperature monitoring
- **Heavy-duty door(s) for ease of use**
 - o Multi-pane argon filled glass doors are energy efficient
 - o ADA-compliant full-length flush mount handles
 - o Self-closing doors stay open at 90 degrees for easy product loading
 - o Heavy-duty stainless steel hinges
 - o Locks standard on all doors



HXR1A/2A-FGE

HXR1A/2A-FGE
06/04/26
Item # 13599

HXR1A-FGE

HXR2A-FGE

Interior

Height	60.24"	
Shelf-dimensions (WxDxH)	21.25" x 26.00"	
Nominal capacity	23.10 ft ³	50.37 ft ³

Exterior

W x D x H (height with 4" casters)	27.5" x 34.5" x 79.5"	55" x 33.5" x 79.5"
Door Opening (WxH)	21.75" x 59.25"	
Clearance	Side: 0" Top: 0" Rear: 3"	
Field reversible doors		

Electrical

Voltage	115V/60/1
HACR/Breaker	15.0 Amps
Voltage Range	104-126V
Electrical Connection (NEMA)	5-15P
<ul style="list-style-type: none"> 10 ft. cord/hospital grade plug 	
Ambient Temp. Range	45°F-80.6°F / 7.2°C - 27°C
Control Set Point Range	31°F-52°F / -0.56°C - +11.1°C

System performance

Amperage	5	8
Energy consump. (kWh/day) @ASHRAE/Energy Star®	1.25/(2.43)	3.47
Heat rejection (BTU/Hr.) @NSF/Energy Star®	317/(639)	513
Approx. nominal compres. BTU/HR(HP)	770(1/4HP)	1545(1/2HP)
Refrigerant / charge amount	R290/(4.6oz)	R290/(4.9oz)

Shipping

Shipping size (L x W x H)	35.5" x 31.5" x 81"	58" x 37.5" x 81"
Approximate shipping weight	357 lbs.	586 lbs.

Alarming


High and low product temperature alarm	audible and visual, user programmable set points in F° or C°
Power failure alarm	audible and visual
Door ajar alarm	audible and visual
Probe error alarm	probe errors are detected by MC controller
Alarm volume	0-10 scale
Low battery alert	audible and visual
Back-up battery status	shows voltage level
Temperature log	settable continuous recording of data
Remote contacts	No/NC standard, located behind front panel

Data logging

Information log	graphs or displays temperature data and displays chronological event data up to 3 months of data.
Data export	USB export capabilities

Controls

Temperature display	7" LCD capacitive touchscreen digital temperature display available in user-programmable F° or C°
Information log	up to 3 months of data/ 170,661 records
3rd party probe access	bottom lower left rear of cabinet; co-molded liquid tight plug (nylon & elastomer) which can be pierced by round wire (1) hard wired (±0.7°F , ±0.4°C)
Product temperature display probe	top probe calibration in 0.1° increments
Temperature probe calibration	4-digit password to prevent interface setting/selection changes
Password protection PIN	programmable
Date and time	20ml
Product simulation bottle size	NTC thermistor type
Refrigeration and defrost probes	multiple detection functions
Refrigeration cycle with probe error	31°F - 52°F / -0.56°C - +11.1°C
Programmable operating range	38°F / 3.3°C
Factory preset	



Warranty

Seven year warranty on labor, parts, and compressor.
Valid in United States, Canada, Puerto Rico and U.S. Territories.
For more information, please visit:
hoshizaki.com/support/warranty/