

VUR60A

Undercounter 60" Refrigerator

VUR60A
06/15/26
Item #13761

VALIANCE[®]

by  HOSHIZAKI

W x D x H

60" x 30" x 33.75"
(including 4" casters)

Item #: _____
Project: _____
Qty: _____
AIA#: _____



VUR60A★



FEATURES

- Engineered to maintain NSF-7 temperatures of 100° ambient
- Stainless steel exterior front, sides, and top
- Front breathing air flow design
- Environmentally friendly R290 hydrocarbon refrigerant
- Spring assisted self-closing doors with stay open feature
- Stainless steel exterior doors, sides, and top
- Single section doors are field reversible (no kit needed)
- Stainless steel interior floor with aluminum sides, rear, and top
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 1 per section. 105 lbs. capacity
- Aluminum shelf supports are adjustable in 1/2" increments
- Standard with 4" casters (two with brakes)
- 9 ft. cord and plug
- Container Qty: 28 (40ft container)

Dimensions / Capacity

One Section VUR60A

Interior Storage Capacity (CF) (AHAM)	15.37 ft ³
Overall Width x Depth (including 1" bumper)	59.75" x 30"
Height (including 4" casters)	34.50"
Door Opening (W x H)	30" x 28"
Depth with Door Open at 90°	59"
Adjustable Shelves	2
Shelf Dimensions (W x D)	27.25" x 16"
Crated Shipping Weight	370 lbs.
Crated Length x Depth x Height	64" x 33" x 41.25"

Electrical / Refrigeration

One Section VUR60A

Voltage	115/60/1
HACR Breaker	15.0 Amps
Electrical Connection (NEMA)	5-15P ⚡
Voltage Range	115-127
Ambient Temp. Range	45° to 100°F
Control Setpoint Range	29.5° to 33.5°F
Amperage	1.2
Energy Consumption (kWh/day) @ASHRAE	.0857
Approx. Nominal Compres. BTU/HR (HP)	826(1/3)
Refrigerant / Charge Amount (oz.)	R290 / (2.8oz)

Options

- 6" Casters (set of 4) (HS-5036) Single overshelf for 60" (HS-5174)
 2.25" Casters (set of 4) (HS-5037) Double overshelf for 60" (HS-5165)

Warranty

- 3 Year - Labor on entire machine.
- 4 Year - Parts on entire machine.
- 5 Year - Parts on Compressor

Valid in United States, Canada, Puerto Rico and U.S. Territories.

Contact factory for warranty in other countries.

If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

We reserve the right to change specifications without notice.


VUR60A

Undercounter 60" Refrigerator


VALIANCE[®]
by  HOSHIZAKI

VUR60A
06/15/26
Item #13761

FRONT VIEW



SIDE VIEW



PLAN VIEW

